

DESCRIPTION

The SA-60D-AS is a 60W Class D amplifier suited for broadcasting paging or background music in schools, shops, offices, factories, mosques, churches and large rooms. It is designed for both wall mount and desk-top installation.

SPECIFICATIONS

* 0 dB = 1 V

Power Source	220 - 240V AC 50/60 Hz
Rated Output	60 W
Power Consumption	100 W (rated output), 18 W (IEC60065)
Frequency Response	20 - 20,000 Hz
Distortion	1% or less
Input	MIC1,2 : -52 dB* , 600 Ω, unbalanced, ϕ6.3 phone jack (2P) AUX1,2: -20 dB * , 10 kΩ, unbalanced, RCA pin jack
Output	Speaker out: 4 Ω
S/N Ratio	MIC1,2: 60 dB or more AUX1,2: 70 dB or more (IEC A-Weighted)
Protection	Power Supply Thermal Shut down Power Amplifier Thermal Shut down Power Amplifier Over Current Each protection can be disabled when its factor is removed.
Indicator	Power LED (Blue)
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Case: Steel plate, Off-white, paint Knob: ABS resin, black
Dimensions	210 (W) × 72 (H) × 180 (D) mm
Weight	1.6 kg

APPEARANCE

