



TS-0622



TS-0622A

Description

The TS-0622 (Chairman unit) and TS-0622A (Delegate unit) are two tabletop discussion & voting microphone, which is designed to work with the conference system controller TS-0604M. The microphone unit is built-in a 2W loudspeaker, a monitor earphone output with attenuator. A dual color indicator for direct visual indication of different service: red for speech and green for apply for speech. Attractive ABS patented design of anti-radio frequency technology to ensure superior sound restoration and voice clarity.

Features

- * Chairman unit TS-0622 with priority control over control the delegate unit.
- * Chairman unit speech is not limited by discussion speech quantity.
- * Chairman unit could be connected to anywhere of the system.
- * Chairman unit has right to allow or reject delegate unit's application for speech.
- * Built-in LCD displays the voting result and contribution mode.
- * Five numeric voting buttons include agree, abstain and oppose contribution.
- * ABS patented design of anti-radio frequency technology for superior sound restoration and voice clarity.
- * Frequency response 20-20,000Hz.
- * Particular high sensitivity microphone design to avoid any low frequency shock.
- * First-level sound restoration and voice clarity gooseneck microphone.
- * Dual color indicator for direct display of different service: red for speech and green for apply speech.
- * Anti-squeal technology, the built-in speaker will be automatically off when microphone is on.
- * Built-in a 2.5W speaker and earphone monitor output & attenuator.
- * All of the microphone units are linked together hand-by-hand by 8 Pins particular cable.
- * With 2 meters aluminium foil and waterline shielded cable of anti-electromagnetic wave interference.
- * Easy microphone ID set up.
- * All of the microphone units are power supplied by the controller by safe DC 24V.

Specifications

| Model | TS-0622 & TS-0622A |
|--------------------|--|
| Description | Chairman/Delegate discussion/voting unit |
| Power Supply | DC 24V powered by controller |
| Connector | 8 Pins particular connector |
| Power Consumption | 3W |
| Earphone | input, 9dBu, 8-32 |
| Directivity | cardioid type |
| Speaker Power | 2W |
| Microphone Type | condenser microphone |
| S/N Ratio | >90dB |
| Crosstalk | 80dB |
| Distortion | <0.1% |
| Equivalent Noise | 20dB |
| Max SPL | 105dB |
| Frequency Response | 20-20KHz |
| Sensitivity | -22dB |
| Dimension (WxHxD) | 225x131x48mm |
| Microphone Length | 415, 480 or 650mm |
| Weight | 0.9kg |