



## Features:

- ✓ Digital audio conference system of discussion function.
- ✓ Digital conference system through RJ45 port and CAT6 cable.
- ✓ Conference system controller with USB on front panel for recording.
- ✓ Ideal use in board room, meeting room, conference room in hotel, office and government.
- ✓ The capacity of system is 100 units and max 1000 units by cascaded more extension controller.
- ✓ Voting, simultaneous interpretation and auto video tracking function are optional functions.
- ✓ Support multiple discussion modes: free, first in first out, and limited discussion.
- ✓ Support free discussion quantity of 1, 2, 3 and 5.
- ✓ With one balanced XLR output, one REC in/out and TEL in/out, RS232 & USB for PC connection.
- ✓ Two way communication system by CAT6 cable/RJ45 port or 8 wire cable/ 8 PIN port.
- ✓ Two RJ45 ports for extension controller, four RJ45 ports for microphone connection.
- ✓ Two 8 PIN ports for extension controller, four 8 PIN ports for microphone connection.
- ✓ Built-in DSP & feedback suppressor & LF/HF filters.
- ✓ With 2.8" LCD display for system program and monitoring.
- ✓ Up to international conference equipment, electrical certification standards of IEC 60914.
- ✓ CS-900V is controller with auto-video tracking function support 6 HD cameras.

## Specifications:

<b>Model</b>	<b>CS-900</b>
<b>Description</b>	Digital Conference System Controller
<b>Function</b>	Discussion & Recording (front panel USB)
<b>Optional Function</b>	Voting, simultaneous interpretation and auto-video tracking system
<b>System Capacity</b>	100 units and 1000 units by cascaded more extension controller
<b>Connection Way</b>	Hand in hand
<b>Power Supply</b>	AC220V or 115V, 50-60Hz
<b>Power Consumption</b>	30W
<b>THD</b>	<0.05%
<b>S/N Ratio</b>	>96dB
<b>Frequency Response</b>	20Hz-20KHz
<b>Connector</b>	Two RJ45 ports for extension controller; four RJ45 ports for microphone Two 8 PIN ports for extension controller, four 8 PIN ports for microphone
<b>Output</b>	With one balanced XLR output, one REC in/out and TEL in/out, RS232 & USB for PC.
<b>Dimension</b>	488(W)×360(D)×84(H)mm
<b>Weight</b>	12.7kg

Digital Conference System (CAT6 & Recording)  
CS-901, Chairman Unit  
CS-902, Delegate Unit



Featur

- ✓ Digital conference system microphone system of discussion function.
- ✓ CS-901 is chairman unit with priority over CS-902 delegate unit.
- ✓ Digital conference system by CAT6 cable and RJ45 port, 8 wired cable and 8 PIN connector as spare use.
- ✓ Super cardioid directive condenser pickup
- ✓ Special anti-jamming circuit design without interference with mobile, wi-fi, Bluetooth and radio system.
- ✓ Each controller supports 10 chairman microphones and 100 delegate microphones.
- ✓ Support multiple discussion modes: free, first in first out, and limited discussion.
- ✓ Support free discussion quantity of 1, 2, 3 and 5.
- ✓ With round ring indicator will be light on when microphone on.
- ✓ Human voice pick up distance up to 15-60cm.
- ✓ Flexible gooseneck microphone of black color.
- ✓ Each microphone with volume attenuator.
- ✓ With 0.96" OLED to display the ID and working status.
- ✓ Power supply direct from digital conference system controller CS-900.

Specification:

Model	CS-901	CS-902
Description	Chairman Unit	Delegate Unit
System Capacity	100 units and 1000 units by cascaded more extension controller	
Connection Way	Hand in hand	
Power Supply	DC24V by controller CS-900	
Voice Pickup Distance	15-60cm	
Sensitivity	-44dB±2dB	
Max SPL	125dB	
THD	<0.05%	
S/N Ratio	>80dB	
Frequency Response	30Hz-20KHz	
Impedance	2k Ohm	
Direction	0°/180°>20dB, 1kHz	
Indicator	Red round ring indicator light on when microphone on	
Gooseneck Length	400mm	
Display	0.96" OLED to display the ID and working status.	
Connector	One RJ45 port by CAT6 cable and one 8 PIN port as spare use	
Frequency Response Mic.	100Hz-15kHz	
Dimension	150(W)×135(D)×53(H)mm	
Weight	0.7kg	