

CV-5000

PROFESSIONAL AMPLIFIER WITH 5000 WATTS OF OUTPUT POWER

PRODUCT OVERVIEW



This field proven amp design is the most muscular yet in the CV Series and is a perfect match for Cerwin-Vega's largest and loudest Passive Speakers and Folded Horns. A true powerhouse, the CV-5000 is capable of driving the most demanding speaker applications including Cerwin-Vega's TS-42 Folded Horn Sub. The 3 RU enclosure is compact and feature-laden, with a design that includes a high-efficiency, variable-speed fan tunnel cooling system, complete LED monitoring of the amplifier's status and comprehensive protection circuitry that guards vital components.

FEATURES

Controls

- Front: Volume control that features a 21 detent potentiometer for each channel
- Rear: Mode selector switch (Parallel/Stereo/Bridged Mono)

HPF: On/Off switch for each channel

Limiter: On/Off switch for each channel

Connectors

- Input: Combo jack electronically balanced 1/4" & XLR male for input link
- Output: 5-way binding post & Speakon® connector for each channel

Indicator: Signal, -20dB, -10dB, 0dB, Clip, Protect & Active

Protection: Short Circuit, Thermal, Current Limit, DC Offset, Current Inrush, RF Protection, Turn On / Turn Off Mute

Cooling: Variable speed fan forced cooling

Specifications & appearance subject to change.

USA: P 954.949.9600 • F 954.949.9590

EUROPE: P +32.2.645.05.00 • F +32.2.645.05.05

CERWIN-VEGA!
The **LOUD** Speaker Company

CV-5000

PROFESSIONAL AMPLIFIER WITH 5000 WATTS OF OUTPUT POWER

PRODUCT OVERVIEW



SPECIFICATIONS

Rated Power	Stereo @ 8 Ω	1100 W
	Stereo @ 4 Ω	1800 W
	Stereo @ 2 Ω	2500 W
	Bridge @ 8 Ω	3600 W
	Bridge @ 4 Ω	5000 W
Input Sensitivity (8 Ω)	1.42V (+5.3dB)	
Input Impedance	20 k Ω Balanced / 10k Ω Unbalanced	
Frequency Response	(+/-3.0 dB) 5Hz – 50kHz	
Class	H , 3 tier	
T.H.D (1 kHz, Rated Power)	< 0.03 % 4 Ω and 8 Ω	
Signal to Noise Ratio (20Hz - 20kHz)	<-100 dB	
Damping Factor (8 Ω , 400 Hz)	> 300	
Power Source	100-240 Vac, 50/60 Hz	
Weight (Net)	Net: 83.3 lbs / 37.2 Kgs / Gross 96 lbs / 43.5 Kgs	
Dimensions (H x W x D)	132 x 482 x 482 mm	