

IP PA & Intercom Emergency Adapter(with Speaker) T-6703(D2)



Applications

The IP Network Emergency Station is suitable for indoor and outdoor embedded installation. One touch to call duty officer or a pre-designated target terminal for intercom communication or background music broadcast.

Features

- * Rectangular embedded design, simple appearance with elegant lines and craft
- * One touch for help, a microphone to call duty room, realizing fast connection, simple and quick operation.
- * With built-in microphone. Built-in 10W a full-range monitor speaker with clear and loud sounds
- * Support hands-free calls and broadcast receiving.
- * Support local one line input; one line audio auxiliary output; externally connect to amplifiers.
- * Support local emergency button signal.
- * Support local electronic door locks and local alarm indicator (select 1 from 2).
- * 12V DC power interface.

Specifications

Model	T-6703(D2)
Network Interface	Standard RJ45 input
Support Agreement	TCP/IP, UDP, IGMP(multicast)
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio Mode	16-bit stereo CD sound quality
Output Frequency	20Hz~16KHz
THD	≤ 0.3%
S/N Ratio	> 70dB
Auxiliary Line Input Level	400mV industry-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Level	1KΩ
Operating Temperature	-20℃~+60℃
Operating Humidity	10%~90%
Power	≤ 15W
Power Supply	DC12V
Dimensions	240x115x50mm
Weight	1Kg

Rear Panel

